

Product Data Sheet

Model identifier	PC-GKH 3119				
Item	Symbol	Value	Unit	Item	Unit
Heat output			Type of heat input, for electric storage local space heaters only		
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	no
Minimum heat output (indicative)	P_{min}	1,00	kW	manual heat charge control with room and / or outdoor temperature feedback	no
Maximum continuous heat output	$P_{max,c}$	2,00	kW	electronic heat charge control with room and / or outdoor temperature feedback	no
Auxiliary electricity consumption			fan assisted heat output		no
At nominal heat output	el_{max}	0,000	kW	Type of heat output / room temperature control	
At minimum heat output	el_{min}	0,000	kW	single stage heat output and no room temperature control	no
In standby mode	el_{SB}	0,00141	kW	Two or more manual stages, no room temperature control	no
			with mechanic thermostat room temperature control		no
			with electronic room temperature control		no
			electronic room temperature control plus day timer		no
			electronic room temperature control plus week timer		yes
			Other control options		
			room temperature control, with presence detection		no
			room temperature control, with open window detection		yes
			with distance control option		yes
			with adaptive start control		no
			with working time limitation		yes
			with black bulb sensor		no
Contact details	Clatronic International GmbH, Industriering Ost 40, 47906 Kempen, Germany				